



TASKWARRIOR

Command Reference
taskwarrior.org

`task [subcommand] [arguments]`

`task shell`

Launches the Taskwarrior interactive shell.

ID

Unique identifier for each task. ID sequences (1,4-10,19) can be given to commands to affect multiple tasks. Without a command, or arguments, displays the IDs "info."

EDITING

`add [tags] [attrs] description`
Adds a new task to the task list.

`log [tags] [attrs] description`
Adds a new completed task to the task list.

`append [tags] [attrs] description`
Appends information to an existing task description.

`prepend [tags] [attrs] description`
Prepends information to an existing task description.

`annotate ID description`
Adds a time-stamped annotation to an existing task.

`denotate ID description`
Deletes an annotation from the specified task. A partial description will delete the first match.

`duplicate ID [tags] [attrs] [description]`
Duplicates the specified task and allows modifications.

`start ID`
Marks the specified task with a start time.

`stop ID`
Removes the start time from the specified task.

`done ID [tags] [attrs] [description]`
Marks the specified task as done.

REPORTS & INFORMATION

`active [tags] [attrs] [description]`
Active tasks matching specified criteria that are incomplete.

`all [tags] [attrs] [description]`
All tasks matching the specified criteria.

`completed [tags] [attrs] [description]`
Completed tasks matching specified criteria.

`minimal [tags] [attrs] [description]`
Provides a minimal listing of tasks with specified criteria.

`ls [tags] [attrs] [description]`
Provides a short listing of tasks with specified criteria.

`list [tags] [attrs] [description]`
Provides a more detailed listing of tasks with specified criteria.

`long [tags] [attrs] [description]`
Provides the most detailed listing of tasks with specified criteria.

`newest [tags] [attrs] [description]`
Shows the newest tasks with specified criteria.

`oldest [tags] [attrs] [description]`
Shows the oldest tasks with specified criteria.

`undo`
Reverts the task list to the most recent action.

`delete ID`
Deletes the specified task from the task list. Can be undone.

`edit ID`
Launches an editor to let you modify all aspects of a task directly. Use with care.

Modifying & Substitutions

`ID [tags] [attrs] [description]`
Modifies the existing task with provided information.

`ID /from/to/`
Performs one substitution on task description and annotation.

`ID /from/to/g`
Performs all substitutions on task description and annotation.

Escaping Special Characters

Quotes, escaping, or the double dash argument allow the use of special characters or commands within a description.

```
$ task add "quoted ' quote"
$ task add escaped \' quote
$ task add -- project:Home needs scheduling
```

`overdue [tags] [attrs] [description]`
Shows all incomplete tasks matching the specified criteria that are beyond their due date.

`recurring [tags] [attrs] [description]`
Shows all recurring tasks matching the specified criteria.

`waiting [tags] [attrs] [description]`
Shows all waiting tasks matching the specified criteria.

`next [tags] [attrs] [description]`
Shows all tasks with upcoming due dates matching the specified criteria.

Information

`info ID`
Shows all data and metadata for the specified task.

`projects`
Lists all project names that are currently used by pending tasks, and the number of tasks for each.

`tags`
Show a list of all tags used.

`summary`
Shows a report of task status by project.

`timesheet [weeks]`
Weekly report of tasks completed and started.

ATTRIBUTES

`+tag|-tag`
Arbitrary words associated with a task. Use + to add a tag and - to remove a tag from a task.

`project:<project-name>`
Specifies the project to which a task is related to.

`priority:H|M|L|N`
Specifies High, Medium, Low and No priority for a task.

`due:<due-date>`
Specifies the due-date of a task.

`recur:<frequency>`
Specifies the frequency of a recurrence of a task.

`until:<end-date-of-`

`recurrence>`
Specifies the Recurrence end-date of a task.

`fg:<color-spec>`
Specifies foreground color.

`bg:<color-spec>`
Specifies background color.

`limit:<number-of-rows>`
Specifies the desired number of tasks a report should show.

`wait:<wait-date>`
Date until task becomes pending.

`history (history.monthly)`
Report of task history by month.

`history.annual`
Report of task history by year.

`ghistory (ghistory.monthly)`
Graphical report of task status by month.

`ghistory.annual`
Graphical report of task status by year.

`calendar [y | due [y] | month year [y] | year]`
Shows a monthly calendar with due tasks marked.

`stats`
Shows task database statistics.

Dates

Exact specification
`due:7/14/2008`
NOTE: Determined by the <dateformat> configuration variable in the task configuration file.

Relative wording
`due:today`
`due:yesterday`
`due:tomorrow`

Day number with ordinal
`due:23rd`

End of week (Friday), month and year
`due:eow`
`due:eom`
`due:eoy`

Next occurring weekday
`due:fri`

Frequencies

`daily, day, 1d, 2d, ...`
Every day or a number of days.

`weekdays`
Mondays, Tuesdays, Wednesdays, Thursdays, Fridays and skipping weekend days.

`weekly, 1w, 2w, ...`
Every week or a number of weeks.

`biweekly, fortnight`
Every two weeks.

`quarterly, 1q, 2q, ...`
Every three months, a quarter, or a number of quarters.

`semiannual`
Every six months.

`annual, yearly, 1y, 2y, ...`
Every year or a number of years.

`biannual, biyearly, 2y`
Every two years.

Attribute Modifiers

`before` (under, below)
`after` (over, above)

`none`
`any` (equals)
`isnt` (not)
`has` (contain)

`hasnt`
`startswith` (left)
`endswith` (right)

`word`
`noword`

task was written by P. Beckingham
Copyright (C) 2006 - 2010 P. Beckingham
distributed under the GNU General Public License.
<<http://www.gnu.org/licenses/gpl-2.0.txt>>



TASKWARRIOR

Command Reference
taskwarrior.org

CONFIGURATION

color [sample]

Displays all possible colors, or a sample.

NOTE: See the wiki and `~/taskrc` for details on configuring colors.

version

Shows the task version number

help

Shows the long usage text.

show [all | substring]"

Shows all the current settings in the task configuration file. If a substring is specified just the settings containing that substring will be displayed.

config [name [value | '']]

Add, modify and remove settings directly in the task configuration.

Configuration Files & Override Options

~/taskrc

User configuration file - see the taskrc man page for details.

~/task

The default directory where task stores its data files. The location can be configured in the configuration file.

~/task/pending.data

The file that contains the tasks that are not yet done.

~/task/completed.data

The file that contains the completed "done" tasks.

~/task/undo.data

The file that contains the information to the "undo" command.

rc:<path-to-alternate-file>

Specifies an alternate configuration file.

task rc.<name>:<value> ...

Specifies individual configuration file overrides.

IMPORT/EXPORT

import [file]

Imports tasks from a variety of formats.

export (export.csv)

Exports all tasks in CSV format. Redirect the output to a file, if you wish to save it, or pipe it to another command.

export.ical

Exports all tasks in iCalendar format.

NOTE: See the wiki for detailed information on importing and exporting.

CREDITS & COPYRIGHT

task was written by P. Beckingham paul@beckingham.net
Copyright (C) 2006 - 2010 P. Beckingham

This Command Reference is based on the task man page, originally written by P.C. Shyamshankar, and has been modified and supplemented by Federico Hernandez.

Thank also to T. Charles Yun.

task is distributed under the GNU General Public License.
See <<http://www.gnu.org/licenses/gpl-2.0.txt>> for more information.

The official site at
<<http://taskwarrior.org>>